



PRAISTON Sp. z o.o.
ul. Górowska 32
64-100 Leszno
Polska

Biuro: +48 65 527 01 67
Serwis: +48 782 844 000
Fax: +48 65 527 01 67

E-mail: biuro@praiston.pl

Koordynator ds. sprzedaży
Krzysztof Wybieralski
+48 882 762 006

kw@praiston.pl



NBVE 60/30 N germicidal lamp (New)

- A brand new product,
- Made in Poland,
- It has a PZH certificate (National Institute of Hygiene),
- NBVE 60/30 N dual-purpose flow germicidal and virucidal lamp without timer,
- The use of energy-saving flow bactericidal and virucidal lamps of the NBVE series is one of the most effective methods of disinfection,
- This device can be used in two ways: when patients and staff are inside (then the airflow function of the lamp is used, and thus the biocidal UV-C radiation does not escape) or when no one is in the room,
- In this case, external irradiators are activated, which emit radiation with a wavelength of 253 nm into the environment, and thus effectively inactivate mold, bacteria, viruses, fungi and any other microorganisms from the irradiated surfaces,
- **Suitable for:**
 - Hospitals (surgery units, treatment rooms, emergency rooms, patients' wards, isolation rooms, A&E places, dirty linen rooms),
 - Clinics (doctor's and treatment rooms),
 - Laboratories,
 - Pharmacies,
 - The following industries: pharmaceutical, food-processing, cosmetics,
 - Hotel industry and gastronomy,
- **Advantages of NBVE 60/30 N germicidal lamp:**
 - Mounting type: W - wall,
 - Significant reduction in power consumption from the grid saves from 200 to 300 zlotys. The variation in this amount is due to the different duration of lamp operation,
 - In flow lamps with an external direct-acting radiator, it is also possible to disinfect the entire room when staff and patients are outside - this is what the dual-functionality of devices of this type is all about,
 - Thanks to the internal radiators, it is also a flow germicidal lamp for air disinfection in the presence of staff and patients,
 - Forced air flow through the UV-C chamber,
 - Guarantees a consistently high degree of air disinfection,
 - Purpose: operating room, patient rooms, laboratories, emergency rooms, waiting rooms, corridors, nurseries, kindergartens and all public gatherings. In general, wherever a high degree of microbiological purity is required and, at the same time, where people must be present,
 - Type of case: acid-resistant sheet metal, which guarantees easy disinfection and cleaning of the lamp,
 - All required certificates,
- **Technical data:**
 - Wall-mounted lamp,
 - Supply voltage: 230 V 50 Hz,
 - Power consumption: 115 W,
 - Internal UV-C emitting element: 2 x 30W,
 - External UV-C emitting element: 1 x 30W,
 - UV-C irradiance at 1 m distance: 100 μ W/cm²,
 - Radiant life: 9000 h,
 - Fan capacity: 132 m³/h,
 - Disinfected volume: 25 - 50 m³,
 - Operating range of the lamp: 10 - 20 m²,
 - Anti-schock safety class: I,
 - Case type: IP 20,
 - Chamber's dimensions: 1125 x 285 x 130 mm,
 - Dimensions: 1190 x 285 x 145 mm,
 - Weight: 9 kg,
- It has a valid Technical Passport,
- Guarantee: 12 months,

