

PRAISTON Sp. z o.o. ul. Górowska 32 64-100 Leszno Polska

Biuro: +48 65 527 01 67 Serwis:+48 782 844 000 Fax: +48 65 527 01 67

E-mail: biuro@praiston.pl

Koordynator ds. sprzedaży Krzysztof Wybieralski +48 882 762 006

kw@praiston.pl



## **ALARIS GW CardinaHealth Volumetric pump (Reconditioned)**

- · Reconditioned (used),
- · Technical condition: very good,
- · Visual condition: very good,
- · Real photos of the product,
- Made in Switzerland,
- Power supply: 230 V,
- Emergency power supply: via 1 new built-in 7.2 V 1.25 Ah battery
- Frequency: 50/60 Hz,
- Power: 10 VA,
- · Alaris GW is a small, lightweight volumetric infusion pump for accurate and reliable infusions,
- · Can be used for intravenous, intra-arterial, subcutaneous and epidural administration of fluids and drugs,
- Designed for use in general and intensive care.
- In-line air detection,
- · Foiled control panel,
- · Built-in rechargeable battery ensures uninterrupted pump operation in case of power loss or patient transport,
- · Housing without protruding knobs and buttons on the front panel for easy maintenance and disinfection,
- · Can be mounted on a tripod,
- · Safety features:
  - BackOff function to reduce post-occlusion bolus,
  - Manual shut-off,
  - Detection of accumulated air in the line,
  - Automatic recognition of intravenous infusion sets,
- · Alarm states:
  - System error,
  - Air in line,
  - Open door.
  - Incorrect infusion line,
  - Open door,
  - Discharged battery,
  - · Occlusion in the upper part,
  - Occlusion in the lower part.
- Equipped with:
  - RS 232 socket for nurse call button,
  - Flow sensor socket,
  - · Holder with clamping screw for mounting on a rail, such as a tripod or bed,
  - · LED screen.
- Specifications:
  - Infusion speed range:
    - Standard mode: 1 999 mL / h,
  - Micro mode: 1 99.9 mL / h,
  - Volume to be administered (VTBI):
    - Standard mode: 1 9999 mL / h,
    - Micro mode: 0.1 999 mL / h,
  - Volume to be administered (VI):
    - Standard and Micro modes: 0 9999 mL,
  - KVO infusion rate: max 5 mL / h or equal to the infusion rate, • Occlusion alarm pressure (at 125 mL / h speed):
    - Low: 250 mmHg,
    - Normal: 350 mmHg,
    - High: 500 mmHg,
  - Bolus delivery during infusion:
    - Bolus delivery rate: 1- 999 mL / h,
    - Bolus volume: 0 99 mL,
- Keypad on control panel in language: ENG,
- Included:
  - User manual in language: PL, EN, DE, CS, BG, ES, FR, IT, NL, PT, ZH (PDF),
  - Power cord,
- · No droplet sensor included,
- Dimensions: 13.5 x 10.5 x 13 cm,
- · Weight: 2 KG,
- Has a current inspection and is ready for operation,
  The basic of Records (Consider Records) and in the second of the s
- Issued Technical Passport (Service Report) valid for 12 months,
- · Warranty:
  - 6-months for domestic market (Poland),
  - 3-months for the international market,
  - Possibility to extend the warranty up to 12-months for domestic and international market for a surcharge,
- Financing options (Poland only): Installments, Leasing, Loan,

If you have any questions, please do not hesitate to contact us!

In case you don't find the product you are interested in, please get in touch with us and we will do our best to find the perfect solution for YOU.



www.praiston.pl