



**PRAISTON Sp. z o.o.**  
ul. Górowska 32  
64-100 Leszno  
Polska

Biuro: +48 65 527 01 67  
Serwis: +48 782 844 000  
Fax: +48 65 527 01 67

E-mail: [biuro@praiston.pl](mailto:biuro@praiston.pl)

Koordinator ds. sprzedaży  
Krzysztof Wybieralski  
+48 882 762 006

[kw@praiston.pl](mailto:kw@praiston.pl)



## RODENSTOCK PHOROVIST 2000 Phoropter (New)

- New,
- Made in Germany,
- Advantages and features of the PHOROVIST 2000 Phoropter:
  - Simple, intuitive operation,
  - Very solid workmanship,
  - Fast and precise,
  - Lenses with high quality coatings,
  - Cross cylinder + rotary prism,
  - Wide range of tests,
  - Close-up test + auxiliary lenses,
  - Convergence system,
- Specifications:
  - Measurement range:
    - -19.00 to + 16.75 D (in 0.25D increments),
    - -29.00 to + 26.75 D (when optional lens is used)
  - Cylinder:
    - 0 to -6.00 D (in 0.25D steps),
    - 0 to -8.00 D (when optional lens is used),
  - PD: 48 to 80 mm,
  - Convergence:  $\infty$  to 400 mm,
  - Prism: 0 to 20  $\Delta$  (step 1  $\Delta$ ),
  - Cylinder axis 0 to 180  $^{\circ}$  (in 5  $^{\circ}$  increments),
- REFRACTOR HEAD:
  - Auxiliary lens: Occluder, pinhole filter, red/green filter, polarizing filter (45 $^{\circ}$ /135 $^{\circ}$ ), fixed cross cylinder lens ( $\pm$  0.50 D), red/white Maddox vertical/horizontal rod, prism ( 6, 10 $\Delta$  I, U), Lens +0.12 D,
  - Cross cylinder:  $\pm$ 0.25 D,
  - Additional lenses: Cylindrical lens -0.12 D, -2.00 D,
  - Retinoscopy: +2.00 D (50 cm),
- Dimensions and Weight:
  - WDH dimensions: 323 x 85 x 315 mm,
  - Weight: Approx. 5.0 kg,
- Has a current Technical Passport issued,
- Warranty 12 months,

