



PRAISTON Sp. z o.o.
ul. Górowska 32
64-100 Leszno
Polska

Biuro: +48 65 527 01 67
Serwis: +48 782 844 000
Fax: +48 65 527 01 67
E-mail: biuro@praiston.pl

Koordynator ds. sprzedaży
Krzysztof Wybieralski
+48 882 762 006
kw@praiston.pl



RODENSTOCK PHOROVIST 2000 Phoropter (New)

- New,
- Made in Germany,
- Advantages and features of the PHOROVIST 2000 Phoropter:
 - Simple, intuitive operation,
 - Very solid workmanship,
 - Fast and precise,
 - Lenses with high quality coatings,
 - Cross cylinder + rotary prism,
 - Wide range of tests,
 - Close-up test + auxiliary lenses,
 - Convergence system,
- Specifications:
 - Measurement range:
 - -19.00 to + 16.75 D (in 0.25D increments),
 - -29.00 to + 26.75 D (when optional lens is used)
 - Cylinder:
 - 0 to -6.00 D (in 0.25D steps),
 - 0 to -8.00 D (when optional lens is used),
 - PD: 48 to 80 mm,
 - Convergence: ∞ to 400 mm,
 - Prism: 0 to 20 Δ (step 1 Δ),
 - Cylinder axis 0 to 180 ° (in 5 ° increments),
- REFRACTOR HEAD:
 - Auxiliary lens: Occluder, pinhole filter, red/green filter, polarizing filter (45°/135°), fixed cross cylinder lens (\pm 0.50 D), red/white Maddox vertical/horizontal rod, prism (6, 10 Δ I, U), Lens +0.12 D,
 - Cross cylinder: \pm 0.25 D,
 - Additional lenses: Cylindrical lens -0.12 D, -2.00 D,
 - Retinoscopy: +2.00 D (50 cm),
- Dimensions and Weight:
 - WDH dimensions: 323 x 85 x 315 mm,
 - Weight: Approx. 5.0 kg,
- Has a current Technical Passport issued,
- Warranty 12 months,

