



PRAISTON Sp. z o.o.
ul. Górowska 32
64-100 Leszno
Polska

Biuro: +48 65 527 01 67
Serwis: +48 782 844 000
Fax: +48 65 527 01 67

E-mail: biuro@praiston.pl

Koordinator ds. sprzedaży
Krzysztof Wybieralski
+48 882 762 006

kw@praiston.pl



RODENSTOCK CX 2000 Autorefractometer with keratometer (New)

- New,
- Made in Germany,
- Product advantages and features:
 - Fully automatic measurement,
 - Innovative solutions,
 - Keratometry measurement,
 - Measurement of pupil and corneal diameter,
 - Automatic centering,
 - Precise measurement,
 - Electrically lifted chin,
 - Integrated printer,
 - Simple operation,
 - Modern and precise technological solutions,
 - Extremely fast,
 - Innovative joystick,
 - Color precise touch screen display,
- Technical data:
- Refractive power measurement:
- CYLINDRICAL REFRACTIVE CAPACITY (C):
- AXIAL ASTIGMATISM (A):
- Corneal measurement:
- Pupil distance measurement:
- Automatic alignment range:
- Main unit:
- Moving part:
- Chin:
- Data output type: RS 232 c
- Display: 5.7" TFT,
- Dimensions and electrical requirements:
 - Spherical (SPH): -25.00 D to +22.00 D (at VD = 12.0 mm),
 - Cylindrical (CYL): 0 D to ±10.00 D (at VD = 12.0 mm),
 - Graduations shown: 0.01 D, 0.12 D, 0.25 D,
 - Measuring range: 0 D to ±10.00 D (at VD=12.0 mm),
 - Graduations shown: 0.01 D, 0.12 D, 0.25 D,
 - Asti. axial angle (AXIS): 0° to 180,
 - Asti. Measurement step: 1°,
 - Minimum pupil Ø: 2.2 mm,
 - Apex distance: 0 mm - 16.0 mm,
 - Measurement time: 0.2 s / one eye (data acquisition time),
 - Curvature (K1, K2, AVG): 5.00 mm to 11.00 mm,
 - Measurement step: 0.01 mm,
 - Refractive power (K1, K2, AVG): 30.68 D to 67.50 D (n = 1.3375),
 - Astigmatism (CYL): 0 D to 10 D (n=1.3375),
 - Measurement step: 0.01 D,
 - Asti. axial angle (AXIS): 0° to 180 °,
 - Asti. Measurement step: 1°,
 - Cornea ø: 3.0 mm / 6.0 mm (at 8.00 mm corneal curvature),
 - Measurement time: 0.1 seconds / one eye (data acquisition time),
 - Measuring range: 50 to 86 mm,
 - Measuring step: 1 mm,
 - Corneal and pupil diameter measurement:
 - Measuring range: 1 to 14 mm,
 - Measuring step: 0.1 mm,
 - Observation range: approx. 15 mm × 9 mm,
 - Top down / left right
 - Direction: 7 mm,
 - Focusing direction: 5 mm,
 - Built-in printer: thermal printer,
 - Range of motion:
 - Front to back: 40 mm,
 - Left-right: 88 mm,
 - Top-bottom: 50 mm,
 - Movable range: 70 mm,
 - Dimensions (WxDxH): 300 × 493 × 466 mm,
 - Weight: approximately 19 kg,
 - Power supply: 100 V AC to 240 V AC,
 - Frequency 50/60 Hz,
 - Power consumption: 130 VA to 150 VA,
- Has a current Technical Passport issued,
- Warranty 12 months,

