



PRAISTON Sp. z o.o.
ul. Górowska 32
64-100 Leszno
Polska

Biuro: +48 65 527 01 67
Serwis: +48 782 844 000
Fax: +48 65 527 01 67

E-mail: biuro@praiston.pl

Koordynator ds. sprzedaży
Krzysztof Wybieralski
+48 882 762 006

kw@praiston.pl



NBVE 110 P germicidal lamp (New)

- A brand new product,
- Made in Poland,
- **The device is 100% safe for people! It has a PZH certificate (National Institute of Hygiene),**
- Germicidal and virucidal flow-through lamp NBVE 60 N: without timer,
- The use of energy-efficient germicidal flow-through lamps of the NBVE series is one of the most effective and safest methods of disinfection,
- The modern design of the NBVE series lamps ensures that harmful UV-C radiation does not get off from the device, so it is safe to use the NBVE series lamps while patients and staff are in the room,
- These devices emit UV-C radiation with a wavelength of 253.7 nm. This radiation has the strongest biocidal properties and irreversibly inactivates bacteria, viruses, molds, fungi and all other microorganisms,
- The process of air purification through the energy-saving NBVE series flow-through lamps is applied by the forced circulation of air through the disinfection chamber, in which the germicidal radiators are located. This flow is performed by a fan built into the lamp.
- **Suitable for:**
 - Hospitals (surgery units, patients' rooms, emergency rooms, patients' wards, isolation rooms, A&E places, dirty linen rooms, etc.),
 - Clinics (doctor's and treatment rooms),
 - Laboratories,
 - Pharmacies,
 - The following industries: pharmaceutical, food-processing, cosmetics,
 - Hotel industry and gastronomy,
- **NBVE 110 P germicidal lamp's advantages:**
 - Mounting type: M- on a mobile tripod,
 - A significant reduction in power consumption which enables to save from 200 to 300 PLN zloty.
 - Tin case: made of acid-resistant material which increases the efficiency of disinfection and allows quick and easy removal of dirt from the surface of the device,
 - While the lamp is operating, the staff and the patients can be inside the room,
 - Flow-through: air flow circulation is performed by a UV-C chamber,
 - Designation: operating units, patients' rooms, laboratories, emergency rooms, waiting rooms, corridors and all crowded places. Generally speaking, wherever a high degree of microbiological cleanliness is required,
 - Fluent and high air disinfection level is guaranteed by tests and is medically certified,
- **Technical data:**
 - The lamp is placed on a mobile tripod,
 - Power supply voltage: 230 V 50 Hz,
 - Energy-saving – power consumption: 115 W,
 - UV-C emitting element: 2 x 55W,
 - Radiant's durability: 9000 h,
 - Fan's efficiency: 199 m³/h,
 - Disinfected capacity: 45 - 90 m³/h,
 - Operating range of the lamp: 18 - 36 m²,
 - Anti-schock safety class: I,
 - Case type: IP 20,
 - Chamber's dimensions: 1125 x 215 x 130 mm,
 - Dimensions: 600 x 1340 x 600 mm,
 - Weight: 13,5 kg,
- It has a valid Technical Passport,
- Guarantee: 12 months,

