



PRAISTON Sp. z o.o.
ul. Górowska 32
64-100 Leszno
Polska

Biuro: +48 65 527 01 67
Serwis: +48 782 844 000
Fax: +48 65 527 01 67

E-mail: biuro@praiston.pl

Koordinator ds. sprzedaży
Krzysztof Wybieralski
+48 882 762 006

kw@praiston.pl



NBVE 60/30 NL germicidal lamp (New)

- A brand new product,
- Made in Poland,
- It has a PZH certificate (National Institute of Hygiene),
- NBVE 60/30 NL dual-purpose flow germicidal lamp without timer,
- The use of energy-saving flow bactericidal and virucidal lamps of the NBVE series is one of the most effective methods of disinfection,
- This device can be used in two ways: when patients and staff are inside (then the airflow function of the lamp is used, and thus the biocidal UV-C radiation does not escape) or when no one is in the room,
- In this case, external irradiators are activated, which emit radiation with a wavelength of 253 nm into the environment, and thus effectively inactivate mold, bacteria, viruses, fungi and any other microorganisms from the irradiated surfaces,
- **Suitable for:**
 - Hospitals (surgery units, treatment rooms, emergency rooms, patients' wards, isolation rooms, A&E places, dirty linen rooms),
 - Clinics (doctor's and treatment rooms),
 - Laboratories,
 - Pharmacies,
 - The following industries: pharmaceutical, food-processing, cosmetics,
 - Hotel industry and gastronomy,
- **Advantages of NBVE 60/30 NL germicidal lamp:**
 - Mounting type: W - wall,
 - L - induction timer with display with indications of 1 hour accuracy (a model proposed as standard for this lamp),
 - LW - electronic counter with a four-pole display with indications with an accuracy of 1 hour and with an acoustic signaling of the moment of replacing the radiator (model mounted on request; used to sum up the working time of the radiators),
 - Effectiveness confirmed by certificates and many tests conducted in specialized microbiological laboratories,
 - It is an energy-saving model that saves up to 300 zloty per month,
 - The external radiant heater responds to disinfection of the room during the absence of employees and patients in the room,
 - Internal irradiator: gives the opportunity to use the lamp while patients and staff are in the room/office,
 - Flow through the UV-C chamber is enabled by a fan built into the disinfection chamber,
 - A consistently high level of air disinfection when using this lamp is guaranteed,
 - Purpose: operating rooms, patient rooms, laboratories, emergency rooms, waiting rooms, corridors,
 - The acid-resistant sheet metal case increases the disinfecting properties,
- **Technical data:**
 - Wall-mounted lamp,
 - Supply voltage: 230 V 50 Hz,
 - Power consumption: 115 W,
 - Internal UV-C emitting element: 2 x 30W,
 - External UV-C emitting element: 1 x 30W,
 - UV-C irradiance at 1 m distance: 100 μ W/cm²,
 - Radiant life: 9000 h,
 - Fan capacity: 132 m³/h,
 - Disinfected volume: 25 - 50 m³,
 - Operating range of the lamp: 10 - 20 m²,
 - Anti-schock safety class: I,
 - Case type: IP 20,
 - Chamber's dimensions: 1125 x 285 x 130 mm,
 - Dimensions: 1190 x 285 x 145 mm,
 - Weight: 9 kg,
- It has a valid Technical Passport,
- Guarantee: 12 months,

