



PRAISTON Sp. z o.o.
ul. Górowska 32
64-100 Leszno
Polska

Biuro: +48 65 527 01 67
Serwis: +48 782 844 000
Fax: +48 65 527 01 67

E-mail: biuro@praiston.pl

Koordinator ds. sprzedaży
Krzysztof Wybieralski
+48 882 762 006

kw@praiston.pl



NBVE 110/55 PL germicidal lamp (New)

- A brand new product,
- Made in Poland,
- It has a PZH certificate (National Institute of Hygiene),
- NBVE 110/55 PL dual-purpose flow germicidal lamp with two operating time meters,
- The use of energy-saving flow bactericidal and virucidal lamps of the NBVE series is one of the most effective methods of disinfection,
- This device can be used in two ways: when patients and staff are inside (then the airflow function of the lamp is used, and thus the biocidal UV-C radiation does not escape) or when no one is in the room,
- In this case, external irradiators are activated, which emit radiation with a wavelength of 253 nm into the environment, and thus effectively inactivate mold, bacteria, viruses, fungi and any other microorganisms from the irradiated surfaces,
- **Suitable for:**
 - Hospitals (surgery units, treatment rooms, emergency rooms, patients' wards, isolation rooms, A&E places, dirty linen rooms),
 - Clinics (doctor's and treatment rooms),
 - Laboratories,
 - Pharmacies,
 - The following industries: pharmaceutical, food-processing, cosmetics,
 - Hotel industry and gastronomy,
- **Advantages of NBVE 110/55 PL germicidal lamp:**
 - Mounting type: M - mobile, on a tripod,
 - For this germicidal lamp, our company offers two types of meters. Standard: L - inductive model with a display with an indication of up to 1 hour. And also LW - electronic counter (mounted on request) with a four-pole display (indication with an accuracy of up to 1 hour; function of acoustic signaling about the need to replace the radiant heaters),
 - The device has all required certificates,
 - The lamp has passed tests in a microbiological laboratory,
 - Type of case: made of acid-resistant sheet metal,
 - Energy-saving model: the use is associated with a significant reduction in electricity consumption,
 - Guarantee of high level of air disinfection,
 - Purpose: the device perfectly fulfills its function in operating rooms, patient rooms, corridors, emergency rooms, nurseries, kindergartens and production sites,
 - The device has three radiant heaters: 1 external allows disinfection of the entire room during the absence of users of the room/office; 2 internal allow safe and effective deactivation of viruses, fungi, mold and other microorganisms during the operation of the office (i.e., when staff and patients are in the room),
 - Forced airflow through the UV-C chamber is an added advantage of this device,
- **Technical data:**
 - The lamp is placed on a mobile tripod,
 - Supply voltage: 230 V 50 Hz,
 - Power consumption: 145 W,
 - Internal UV-C emitting element: 2 x 55W,
 - External UV-C emitting element: 1 x 55W,
 - UV-C irradiance at 1 m distance: 150 μ W/cm²,
 - Radiant life: 9000 h,
 - Fan capacity: 199 m³/h,
 - Disinfected volume: 45 - 90 m³,
 - Operating range of the lamp: 18 - 36 m²,
 - Anti-schock safety class: I,
 - Case type: IP 20,
 - Chamber's dimensions: 1125 x 285 x 130 mm,
 - Dimensions: 600 x 1270 x 600 mm,
 - Weight: 13,5 kg,
- It has a valid Technical Passport,
- Guarantee: 12 months,

