



PRAISTON Sp. z o.o.
ul. Górowska 32
64-100 Leszno
Polska

Biuro: +48 65 527 01 67
Serwis: +48 782 844 000
Fax: +48 65 527 01 67

E-mail: biuro@praiston.pl

Koordinator ds. sprzedaży
Krzysztof Wybieralski
+48 882 762 006

kw@praiston.pl



NBV 30 NL germicidal lamp (New)

- A brand new product,
- Made in Poland,
- Direct-acting germicidal lamp NBV 30 NL with timer without display,
- The device has a counter with a microprocessor, without a display, with an acoustic indication when the lamp is replaced,
- **The use of the device:**
 - Medical institutions,
 - Hospitals,
 - Pharmaceutical industry,
 - Food industry,
 - Cosmetics industry,
- **Advantages of NBV 30 NL germicidal lamp:**
 - L-counter digital counter with a microprocessor, without a display with an acoustic indication of the moment of replacing the radiator. This type of the counter is designed for direct-acting lamps,
 - Mounting method: W - wall-mounted,
 - With this germicidal lamp, you will raise the level of microbiological purity,
 - Emitted radiation: UV-C with a wavelength of 253.7 nm,
 - Purpose: deactivation of viruses, molds, fungi and microorganisms,
 - Effect: effective disinfection of air and surfaces,
 - Reflector: this element is made of aluminum, which guarantees the highest quality of this device,
 - Purpose: the germicidal lamp is used in medical institutes, hospitals and clinics, as well as in pharmaceutical, food and cosmetic industries,
 - The effectiveness of this lamp has been confirmed by tests; it is also proven by numerous certificates,
 - It is recommended to turn on the lamp in rooms of standard height (up to 3m) for about 2-8 hours a day, and for 15 to 20 minutes before treatments,
- **Technical data:**
 - Wall mounted lamp,
 - Supply voltage: 230 V 50 Hz,
 - Power consumption: 33 W,
 - UV-C emitting element: 1 x 30 W,
 - UV-C irradiance at 1 m distance: 2.3 W / m²,
 - Radiant life: 9000 h,
 - Disinfectable area: 12 - 15 m²,
 - Lamp rotation (exposure angle can be adjusted): 200°,
 - Anti-schock safety class: I,
 - Case type: IP 20,
 - Operation type: continuous,
 - Chamber's dimensions: 960 x 85 x 135 mm,
 - Chamber's weight: 3 kg,
 - The extension's length: 120 mm,
- It has a valid Technical Passport,
- Guarantee: 12 months,

