



**PRAISTON Sp. z o.o.**  
ul. Górowska 32  
64-100 Leszno  
Polska

Biuro: +48 65 527 01 67  
Serwis: +48 782 844 000  
Fax: +48 65 527 01 67

E-mail: [biuro@praiston.pl](mailto:biuro@praiston.pl)

Koordynator ds. sprzedaży  
Krzysztof Wybieralski  
+48 882 762 006

[kw@praiston.pl](mailto:kw@praiston.pl)



## **NBV 2x30 NL germicidal lamp (New)**

- A brand new product,
- Made in Poland,
- Direct-acting germicidal lamp NBV 2x30 NL with timer without display,
- The device has a counter with a microprocessor, without a display with an acoustic indication of the moment of replacing the radiator,
- It has a CL-02 reader to read the current status of the counter,
- **The use of the device:**
  - Medical institutions,
  - Hospitals,
  - Pharmaceutical industry,
  - Food industry,
  - Cosmetics industry,
- **Advantages of NBV 2x30 NL germicidal lamp:**
  - Counter: L-counter digital counter with a microprocessor, without a display. It has an audible signaling function for the moment of replacing the radiator. This model is installed in direct-acting lamps.
  - Lamp mounting method: W - wall-mounted,
  - The main task of the product is to raise and maintain the level of microbiological purity in the room,
  - The direct action lamp emits UV-C radiation with a wavelength of 253.7 nm,
  - The device irreversibly inactivates bacteria, viruses, molds, fungi and all other microorganisms,
  - The germicidal lamp completely disinfects the air and surface,
  - The lamp reflector is made of high-quality reflective aluminum,
  - The device is used in operating rooms, treatment rooms, hospitals, laboratories and food, pharmaceutical and cosmetic industries, treatment rooms, bandaging rooms, patient rooms, clinics, laboratories, pharmacies,
  - The performance of germicidal lamps is confirmed by tests and all required certificates,
- **Technical data:**
  - Wall mounted lamp,
  - Supply voltage: 230 V 50 Hz,
  - Power consumption: 66 W,
  - UV-C emitting element: 2x30 W,
  - UV-C irradiance at 1 m: 3.6 W / m<sup>2</sup>,
  - Radiant life: 9000 h,
  - Disinfectable area: 18 - 22 m<sup>2</sup>,
  - Lamp rotation (exposure angle can be adjusted): 200°,
  - Anti-schock safety class: I,
  - Case type: IP 20,
  - Operation type: continuous,
  - Chamber's dimensions: 960 x 85 x 145 mm,
  - Chamber's weight: 5 kg,
  - The extension's length: 120 mm,
  - Counter type: without a display,
- It has a valid Technical Passport,
- Guarantee: 12 months,

