



PRAISTON Sp. z o.o.
ul. Górowska 32
64-100 Leszno
Polska

Biuro: +48 65 527 01 67
Serwis: +48 782 844 000
Fax: +48 65 527 01 67

E-mail: biuro@praiston.pl

Koordynator ds. sprzedaży
Krzysztof Wybieralski
+48 882 762 006

kw@praiston.pl



NBV 2x30 NL germicidal lamp (New)

- A brand new product,
- Made in Poland,
- Direct-acting germicidal lamp NBV 2x30 NL with timer without display,
- The device has a counter with a microprocessor, without a display with an acoustic indication of the moment of replacing the radiator,
- It has a CL-02 reader to read the current status of the counter,
- **The use of the device:**
 - Medical institutions,
 - Hospitals,
 - Pharmaceutical industry,
 - Food industry,
 - Cosmetics industry,
- **Advantages of NBV 2x30 NL germicidal lamp:**
 - Counter: L-counter digital counter with a microprocessor, without a display. It has an audible signaling function for the moment of replacing the radiator. This model is installed in direct-acting lamps.
 - Lamp mounting method: W - wall-mounted,
 - The main task of the product is to raise and maintain the level of microbiological purity in the room,
 - The direct action lamp emits UV-C radiation with a wavelength of 253.7 nm,
 - The device irreversibly inactivates bacteria, viruses, molds, fungi and all other microorganisms,
 - The germicidal lamp completely disinfects the air and surface,
 - The lamp reflector is made of high-quality reflective aluminum,
 - The device is used in operating rooms, treatment rooms, hospitals, laboratories and food, pharmaceutical and cosmetic industries, treatment rooms, bandaging rooms, patient rooms, clinics, laboratories, pharmacies,
 - The performance of germicidal lamps is confirmed by tests and all required certificates,
- **Technical data:**
 - Wall mounted lamp,
 - Supply voltage: 230 V 50 Hz,
 - Power consumption: 66 W,
 - UV-C emitting element: 2x30 W,
 - UV-C irradiance at 1 m: 3.6 W / m²,
 - Radiant life: 9000 h,
 - Disinfectable area: 18 - 22 m²,
 - Lamp rotation (exposure angle can be adjusted): 200°,
 - Anti-schock safety class: I,
 - Case type: IP 20,
 - Operation type: continuous,
 - Chamber's dimensions: 960 x 85 x 145 mm,
 - Chamber's weight: 5 kg,
 - The extension's length: 120 mm,
 - Counter type: without a display,
- It has a valid Technical Passport,
- Guarantee: 12 months,

