PRAISTON Sp. z o.o.
ul. Górowska 32
64-100 Leszno
Polska

Biuro: +48 65 527 01 67
Serwis:+48 782 844 000
Fax: +48 65 527 01 67

E-mail: biuro@praiston.pl

Koordynator ds. sprzedaży
Krzysztof Wybieralski
+48 882 762 006

kw@praiston.pl

NBV 15 N LW germicidal lamp (New)

• A brand new product,
• Made in Poland,
• NBV 15 NLW direct-acting germicidal lamp with 4-field display timer,
• Equipped with a digital counter with a microprocessor that has a 4-field LED display. Care has been taken to ensure that this model audibly signals when the radiant heater is replaced,
• A big plus of this type of meter is that it can be independently connected to previously purchased direct-acting and flow lamps,
• The air and surface in the room where this lamp was used are effectively disinfected,
• **The use of the device:**
  ◦ Medical institutions,
  ◦ Hospitals,
  ◦ Pharmaceutical industry,
  ◦ Food industry,
  ◦ Cosmetics industry,
• **Advantages of NBV 15 N LW germicidal lamp:**
  ◦ Counter type: LW - digital counter with a microprocessor with a 4-field LED display. Great care has been taken to ensure that this model audibly signals the moment of replacement of the radiator. A big plus of this type of the counter is the possibility of independent connection to previously purchased direct-acting and flow lamps,
  ◦ Mounting method: W - wall-mounted,
  ◦ Designed to raise and maintain the level of microbiological purity of rooms,
  ◦ Emitted radiation: UV-C with a wavelength of 253.7 nm,
  ◦ Irreversibly deactivate bacteria, viruses, molds, fungi and all other microorganisms.
  ◦ The air and surface in the room where this lamp has been used are effectively disinfected,
  ◦ Reflector made of reflective aluminum of very high quality,
  ◦ Designed for the use in operating rooms, treatment rooms, bandaging rooms, patient rooms, clinics, laboratories, pharmacies, pharmaceutical, food and cosmetic industries,
  ◦ Effectiveness of germicidal lamps confirmed by tests,
  ◦ All required certificates,
• **Technical data:**
  ◦ Wall mounted lamp,
  ◦ Supply voltage: 230 V 50 Hz,
  ◦ Power consumption: 18 W,
  ◦ UV-C emitting element: 2x15 W,
  ◦ UV-C irradiance at 1 m distance: 0.9 W / m2,
  ◦ Radiant life: 9000 h,
  ◦ Disinfectable area: 6 - 8 m2,
  ◦ Lamp rotation (exposure angle can be adjusted): 200°,
  ◦ Anti-schock safety class: I,
  ◦ Case type: IP 20,
  ◦ Operation type: continuous,
  ◦ Chamber’s dimensions: 500 x 85 x 135 mm,
  ◦ Chamber’s weight: 2 kg,
  ◦ The extension’s length: 120 mm,
  ◦ Counter type: with 4-field display,
• It has a valid Technical Passport,
• Guarantee: 12 months,