



**PRAISTON Sp. z o.o.**  
ul. Górowska 32  
64-100 Leszno  
Polska

Biuro: +48 65 527 01 67  
Serwis: +48 782 844 000  
Fax: +48 65 527 01 67

E-mail: [biuro@praiston.pl](mailto:biuro@praiston.pl)

Koordinator ds. sprzedaży  
Krzysztof Wybieralski  
+48 882 762 006

[kw@praiston.pl](mailto:kw@praiston.pl)



## **NBV 15 P LW germicidal lamp (New)**

- A brand new product,
- Made in Poland,
- NBV 15 PLW direct-acting germicidal lamp with 4-field display timer,
- Equipped with a digital counter with a microprocessor that has a 4-field LED display. Great care has been taken to ensure that this model audibly signals when the radiant heater is replaced,
- A big advantage of this type of meter is that it can be independently connected to previously purchased direct-acting and flow lamps,
- The air and surface in the room where this lamp was used are effectively disinfected,
- **The use of the device:**
  - Medical institutions,
  - Hospitals,
  - Pharmaceutical industry,
  - Food industry,
  - Cosmetics industry,
- **Advantages of NBV 15 P LW germicidal lamp:**
  - Counter type: LW - digital counter with a microprocessor with a 4-field LED display, with an acoustic indication of the moment of replacement of the radiator. It is possible to independently connect this model to previously purchased direct-acting and flow lamps,
  - Mounting method: M - mobile on a tripod,
  - The result of using this device is to increase the level of microbiological purity of the premises,
  - Emitted radiation: UV-C with a wavelength of 253.7 nm,
  - Irreversibly deactivate bacteria, viruses, molds, fungi and all other microorganisms,
  - The air and surface in the room where this lamp has been used are effectively disinfected,
  - High-quality reflector (material: reflective aluminum),
  - Purpose: the use in operating rooms (and other hospital rooms), in treatment rooms, as well as in the food, pharmaceutical and cosmetic industries,
  - The effectiveness of this device is confirmed by tests and numerous certificates,
- **Technical data:**
  - The lamp is placed on a mobile tripod,
  - Supply voltage: 230 V 50 Hz,
  - Power consumption: 18 W,
  - UV-C emitting element: 15 W,
  - UV-C irradiance at 1 m distance: 0.9 W / m<sup>2</sup>,
  - Radiant life: 9000 h,
  - Disinfectable area: 6 - 8 m<sup>2</sup>,
  - Lamp rotation (exposure angle can be adjusted): 270°,
  - Anti-schock safety class: I,
  - Case type: IP 20,
  - Operation type: continuous,
  - Chamber's dimensions: 500 x 85 x 135 mm,
  - Chamber's weight: 2 kg,
  - The extension's length: 1800 mm,
  - Counter type: with 4-field display,
- It has a valid Technical Passport,
- Guarantee: 12 months,

