



PRAISTON Sp. z o.o.
ul. Górowska 32
64-100 Leszno
Polska

Biuro: +48 65 527 01 67
Serwis: +48 782 844 000
Fax: +48 65 527 01 67

E-mail: biuro@praiston.pl

Koordinator ds. sprzedaży
Krzysztof Wybieralski
+48 882 762 006

kw@praiston.pl



NBV 15 P LW germicidal lamp (New)

- A brand new product,
- Made in Poland,
- NBV 15 PLW direct-acting germicidal lamp with 4-field display timer,
- Equipped with a digital counter with a microprocessor that has a 4-field LED display. Great care has been taken to ensure that this model audibly signals when the radiant heater is replaced,
- A big advantage of this type of meter is that it can be independently connected to previously purchased direct-acting and flow lamps,
- The air and surface in the room where this lamp was used are effectively disinfected,
- **The use of the device:**
 - Medical institutions,
 - Hospitals,
 - Pharmaceutical industry,
 - Food industry,
 - Cosmetics industry,
- **Advantages of NBV 15 P LW germicidal lamp:**
 - Counter type: LW - digital counter with a microprocessor with a 4-field LED display, with an acoustic indication of the moment of replacement of the radiator. It is possible to independently connect this model to previously purchased direct-acting and flow lamps,
 - Mounting method: M - mobile on a tripod,
 - The result of using this device is to increase the level of microbiological purity of the premises,
 - Emitted radiation: UV-C with a wavelength of 253.7 nm,
 - Irreversibly deactivate bacteria, viruses, molds, fungi and all other microorganisms,
 - The air and surface in the room where this lamp has been used are effectively disinfected,
 - High-quality reflector (material: reflective aluminum),
 - Purpose: the use in operating rooms (and other hospital rooms), in treatment rooms, as well as in the food, pharmaceutical and cosmetic industries,
 - The effectiveness of this device is confirmed by tests and numerous certificates,
- **Technical data:**
 - The lamp is placed on a mobile tripod,
 - Supply voltage: 230 V 50 Hz,
 - Power consumption: 18 W,
 - UV-C emitting element: 15 W,
 - UV-C irradiance at 1 m distance: 0.9 W / m²,
 - Radiant life: 9000 h,
 - Disinfectable area: 6 - 8 m²,
 - Lamp rotation (exposure angle can be adjusted): 270°,
 - Anti-schock safety class: I,
 - Case type: IP 20,
 - Operation type: continuous,
 - Chamber's dimensions: 500 x 85 x 135 mm,
 - Chamber's weight: 2 kg,
 - The extension's length: 1800 mm,
 - Counter type: with 4-field display,
- It has a valid Technical Passport,
- Guarantee: 12 months,

