



**PRAISTON Sp. z o.o.**  
ul. Górowska 32  
64-100 Leszno  
Polska

Biuro: +48 65 527 01 67  
Serwis: +48 782 844 000  
Fax: +48 65 527 01 67

E-mail: [biuro@praiston.pl](mailto:biuro@praiston.pl)

Koordynator ds. sprzedaży  
Krzysztof Wybieralski  
+48 882 762 006

[kw@praiston.pl](mailto:kw@praiston.pl)



## **NBV 30 N LW germicidal lamp (New)**

- A brand new product,
- Made in Poland,
- NBV 30 NLW direct-acting germicidal lamp with 4-field display timer,
- It is equipped with a digital counter with a microprocessor having a 4-field LED display, with an acoustic indication when the lamp is replaced,
- Irreversibly deactivates bacteria, viruses, molds, fungi and all other microorganisms,
- In addition, it has a high-quality reflector made of reflective aluminum,
- Turning the lamp on for just 20 minutes brings a rapid air disinfection effect between treatments.
- **The use of the device:**
  - Medical institutions,
  - Hospitals,
  - Pharmaceutical industry,
  - Food industry,
  - Cosmetics industry,
- **Advantages of NBV 30 N LW germicidal lamp:**
  - Counter type: LW - digital counter with a microprocessor with 4-field LED display, with acoustic indication of the moment of replacement of the radiator. Can be independently connected to previously purchased direct-acting and flow lamps,
  - Mounting method: W - wall-mounted,
  - The result of using this device is to increase the level of microbiological purity of the premises,
  - Emitted radiation: UV-C with a wavelength of 253.7 nm,
  - Irreversibly deactivate bacteria, viruses, molds, fungi and all other microorganisms,
  - The air and surface in the room where this lamp has been used are effectively disinfected,
  - High-quality reflector (material: reflective aluminum),
  - Purpose: the use in operating rooms (and other hospital rooms), in treatment rooms, as well as in the food, pharmaceutical and cosmetic industries,
  - The effectiveness of this device is confirmed by tests and numerous certificates,
- **Technical data:**
  - Wall mounted lamp,
  - Supply voltage: 230 V 50 Hz,
  - Power consumption: 33 W,
  - UV-C emitting element: 1 x 30 W,
  - UV-C irradiance at 1 m distance: 2.3 W / m<sup>2</sup>,
  - Radiant life: 9000 h,
  - Disinfectable area: 12 - 15 m<sup>2</sup>,
  - Lamp rotation (exposure angle can be adjusted): 200°,
  - Anti-schock safety class: I,
  - Case type: IP 20,
  - Operation type: continuous,
  - Chamber's dimensions: 960 x 85 x 135 mm,
  - Chamber's weight: 3 kg,
  - The extension's length: 120 mm,
  - Counter type: with 4-field display,
- It has a valid Technical Passport,
- Guarantee: 12 months,

