PRAISTON Sp. z o.o.
ul. Górowska 32
64-100 Leszno
Polska

Biuro: +48 65 527 01 67
Serwis:+48 782 844 000
Fax: +48 65 527 01 67

E-mail: biuro@praiston.pl

Koordynator ds. sprzedaży
Krzysztof Wybieralski
+48 882 762 006

kw@praiston.pl

NBV 2x30 N LW germicidal lamp (New)

• A brand new product,
• Made in Poland,
• NBV 2x30 NLW direct-acting germicidal lamp with 4-field display timer,
• The lamp is equipped with a digital counter with a microprocessor, which has a 4-field LED display, with an acoustic indication of the moment of replacing the radiator,
• This device emits radiation: UV-C with a wavelength of 253.7 nm,
• **The use of the device:**
  ◦ Medical institutions,
  ◦ Hospitals,
  ◦ Pharmaceutical industry,
  ◦ Food industry,
  ◦ Cosmetics industry,
• **Advantages of NBV 30 N LW germicidal lamp:**
  ◦ The effectiveness of this lamp is confirmed by numerous tests and all required certificates,
  ◦ Counter: LW-digital counter with a microprocessor, which is equipped with a 4-field LED display. The functionality of this model is also enhanced by the possibility to independently connect it to previously purchased direct-action and flow lamps,
  ◦ Lamp mounting method: W - wall-mounted,
  ◦ The main task of the product is to raise and maintain the level of microbiological purity in the room,
  ◦ This device emits radiation: UV-C with a wavelength of 253.7 nm,
  ◦ Direct-acting germicidal lamp irreversibly deactivates bacteria, viruses, molds, fungi and all other microorganisms,
  ◦ The effect of using this device: disinfection of air and surfaces,
  ◦ Lamp reflector: made of high-quality reflective aluminum,
  ◦ Purpose: for operating rooms, medical and treatment rooms, as well as food, pharmaceutical and cosmetic industry rooms,
• **Technical data:**
  ◦ Wall mounted lamp,
  ◦ Supply voltage: 230 V 50 Hz,
  ◦ Power consumption: 66 W,
  ◦ UV-C emitting element: 2 x 30 W,
  ◦ UV-C irradiance at 1 m distance : 3.6 W / m2,
  ◦ Radiant life: 9000 h,
  ◦ Disinfectable area: 18 - 22 m2,
  ◦ Lamp rotation (exposure angle can be adjusted): 200°,
  ◦ Anti-schock safety class: I,
  ◦ Case type: IP 20,
  ◦ Operation type: continuous,
  ◦ Chamber’s dimensions: 960 x 85 x 145 mm,
  ◦ Chamber’s weight: 5 kg,
  ◦ The extension’s length: 120 mm,
  ◦ Counter type: with 4-field display,
• It has a valid Technical Passport,
• Guarantee: 12 months,