



PRAISTON Sp. z o.o.
ul. Górowska 32
64-100 Leszno
Polska

Biuro: +48 65 527 01 67
Serwis: +48 782 844 000
Fax: +48 65 527 01 67

E-mail: biuro@praiston.pl

Koordynator ds. sprzedaży
Krzysztof Wybieralski
+48 882 762 006

kw@praiston.pl



NOUVAG Dispenser DP 30 infusion pump (New)

New

Swiss production,

DP 30 is a universal pump used for tumescent anesthesia, in endovascular procedures, liposuction and others,

The DP 30 pump has a wide field to be used wherever precise and fast fluids are needed. It was designed so that you can easily adjust its parameters to the procedure,

The percentage of infiltration is controlled by a rotary potentiometer and foot pedal (up to 17 l / min),

The pedal in the basic ON / OFF version allows you to start the pump (enable / disable) to the parameter set on the pump control panel,

The advantages of the DP 30 Dispenser infusion pump:

The best price-performance ratio,

Easy operation at low maintenance costs,

Time-saving compared to the time-consuming injection of traditional infiltration,

Stepless and precise regulation of infiltration performance,

Reliable and proven technology,

Ergonomic casing - the lightest and smallest housing in its class and easy to clean surfaces,

On / Off control light - green LED indicates whether the device is switched on,

Integrated liquid container - a standard bottle of infiltration solution is conveniently mounted on the plug-in holder.

Easy pipe configuration - wide opening compartment for easy pipe positioning,

Low noise level of the pump drive - the infiltration tube is easy to integrate and the internal pump operates at low noise levels,

Access to the pump from the front - access to the pump with just one hand is done by pressing the button next to the display, thus without unintentional movement of the device,

Accurate pump performance - repeatable infiltration performance due to a scaled regulator,

Standard equipment:

Control unit,

Set of wires,

Power cord,

Foot switch ON / OFF,

Technical data:

Liquid flow up to 17 l / min,

Power consumption 40 VA,

115/230 V, 50-60 Hz power supply,

Maximum pressure 1.5 bar,

Dimensions 260 x 250 x 110 mm,

Net weight 2.5 kg,

Has a current Technical Passport issued

12 months warranty

