



PRAISTON Sp. z o.o.
ul. Górowska 32
64-100 Leszno
Polska

Biuro: +48 65 527 01 67
Serwis: +48 782 844 000
Fax: +48 65 527 01 67

E-mail: biuro@praiston.pl

Koordinator ds. sprzedaży
Krzysztof Wybieralski
+48 882 762 006

kw@praiston.pl



AEOMED SHANGRILA 590 respirator - ventilator (Reconditioned)

Used, perfect technical condition,
Production P.R.C (2013)
Power supply: 230 V,
Frequency: 50/60 Hz,
Power: 65 VA,
Built-in electronic device for mixing air and oxygen, ensuring accurate and stable FiO2 output,
Durable and accurate flow sensor,
Integrated exhalation valve, easy to sterilize,
Ventilation of reserve apnea,
Equipped with a 10.4 TFT color screen,
Ventilation type: VCV, PVC,
Ventilation mode: A / C, SIGH, SIMV (SIMV + PSV), SPONT + PSV,
Tidal volume: 0-1500mL,
Breath: 4-100 minutes per minute,
SIMV rate: 1-40 bpm,
Time of inspiration: 0.1-12s,
Hold time: 0-4s,
Trigger sensitivities: -20-0cmH2O,
PSV: 0-60cmH2O,
Pressure range: 5-60cmH2O,
High pressure: 20-80cmH2O,
Low pressure: 0-20cmH2O,
Shape of ventilation: Square shape and slowdown,
PEEP: 0-40cmH2O,
FiO2: 21% -100%,
Alarm silence: ≤120s,
Monitored parameters: Vti, Vte, MV, FiO2, Ppeak, Pmean, PEEP, Ftot, Fspont, MVspont,
Presented waveforms: PT, FT,
Alarm: O2 failure, air failure, MV / low limit, upper Vt limit, Fspont upper limit, Paw upper / lower value, apnea, FiO2 / low limit, power failure,
Max. alarm: 100,
Safety valve: ≤8Kpa,
Patient type: Adults and children,
Included:
Heated humidifier INSPIRED MEDICAL Model VHB 10,
Power supply: 230 V,
Frequency: 50/60 Hz,
Power: 100 W,
One knob for manual temperature control,
9-step temperature control range,
Overall dimensions:
350 x 400 x 300 mm (without compressor),
490 x 450 x 1300 mm (with compressor),
Has a current Technical Passport issued,
1-month warranty

