



PRAISTON Sp. z o.o.
ul. Górowska 32
64-100 Leszno
Polska

Biuro: +48 65 527 01 67
Serwis: +48 782 844 000
Fax: +48 65 527 01 67

E-mail: biuro@praiston.pl

Koordynator ds. sprzedaży
Krzysztof Wybieralski
+48 882 762 006

kw@praiston.pl



SURTRON FLASH 120 surgical diathermy (New)

New

Italian production,

It has bipolar electrocoagulation with constant power emission,

Is a high-frequency radiosurgical apparatus intended for precise monopolar, bipolar and micro-surgical procedures without tissue changes

It is intended mainly for treatment rooms, small operating rooms, outpatient clinics and endoscopic laboratories.

The devices are equipped with a number of functions facilitating work such as: remembering by the device of the last used operating parameters, adjusting the volume of the device operation signaling.

The diathermy is additionally characterized by high ergonomics: the device can be activated by means of foot pedals and buttons on the handle, while the change of the set modes of the device can be controlled from the front panel level or also using the buttons located on the working handle.

It enables electronic reading of delivered power along with monitoring of operational functions by a microcontroller guarantees complete reliability of working conditions.

Programs for diathermy:

CUT smooth cut,

ENCHACE coagulation cut,

BLEND mixed cutting,

FORCED COAG forced coagulation,

SOFT COAG soft (white) coagulation without carbonization,

BIPOLAR COAG bipolar coagulation,

BIPOLAR ABL bipolar ablation,

Application:

Otolaryngology,

Veterinary medicine,

Vascular surgery,

Urology,

Pediatric surgery,

Plastic surgery,

Endoscopy,

Pulmonology,

Neurosurgery,

General operations,

Dermatology,

Gynecology,

Dentistry,

Equipment:

Reusable handle with buttons,

Microsurgical handle,

Set of various 5 cm electrodes (10 pcs),

Needles for microsurgery / Hair removal (5 items),

7 cm erasers (3 pcs),

6 cm / 4 mm ball electrode (3 pcs),

Needle electrode 7 cm (3 pcs),

Neutral electrode cable,

120x160 mm passive metal electrode,

Single-sided two-sided passive electrodes,

Disposable neutral electrodes (2 pcs),

Waterproof foot switch

5 m power cable.

Technical data:

Passive electrode - F,

Choose between 115-230 Vac,

Operating frequency - 600 kHz,

Maximum power consumption 300 VA,

Weight - 6 kg

Dimensions of the device WxHxD - 370x144x319 mm,

Has a valid Technical Passport issued,

12 months warranty

